

VIKANE* GAS FUMIGANT

Emergency Phone: 800-992-5994 Dow AgroSciences LLC Indianapolis, IN 46268

Effective Date: 5/22/01 Product Code: 91503 MSDS: 000506

1. PRODUCT AND COMPANY IDENTIFICATION:

PRODUCT: Vikane* Gas Fumigant

COMPANY IDENTIFICATION:

Dow AgroSciences 9330 Zionsville Road Indianapolis, IN 46268-1189

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Sulfuryl fluoride

CAS# 002699-79-8

99.8%

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not 'Hazardous' per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

3. HAZARDOUS IDENTIFICATIONS:

EMERGENCY OVERVIEW

Hazardous Chemical. Colorless, odorless compressed gas. Evacuate immediate area if leak occurs. Excessive vapor concentrations are attainable and a single exposure may cause death. Toxic to pets, fish, wildlife, and avian. **EMERGENCY PHONE NUMBER:** 800-992-5994

POTENTIAL HEALTH EFFECTS: This section includes possible adverse effects, which could occur if this material is not handled in the recommended manner.

EYE: Essentially non-irritating to eyes. If liquid contacts eye, evaporation may cause frostbite-type injury due to rapid cooling.

SKIN: Essentially non-irritating to skin. If liquid contacts skin, evaporation may cause frostbite-type injury due to rapid cooling. Skin absorption is unlikely due to physical properties.

INGESTION: Single dose oral toxicity is moderate. The oral LD $_{50}$ for rats is 100 mg/kg. Ingestion is unlikely due to physical state.

THIS INFORMATION WAS PROVIDED TO THE INDUSTRIAL FUMIGANT COMPANY BY THE MANUFACTURER. IFC MAKES NO CLAIMS OR WARRANTIES TO ITS ACCURACY.

INHALATION: Excessive vapor concentrations are attainable and a single exposure may cause death. Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs. The LC₅₀ for a 4-hour exposure for rats is 991-1122 ppm.

systemic (other target organ) effects: In animals, effects have been reported on the following organs: brain, central nervous system, kidney, lung, respiratory tract and thyroid gland. Observations in animals include convulsions and tremors. May cause fluorosis of teeth and bones.

CANCER INFORMATION: Did not cause cancer in laboratory animals.

TERATOLOGY (BIRTH DEFECTS): Birth defects are unlikely. Exposures having no effect on the mother should have no effect on the fetus. Did not cause birth defects in animals; other effects were seen in the fetus only at doses which caused toxic effects to the mother.

REPRODUCTIVE EFFECTS: In animal studies, has been shown not to interfere with reproduction.

4. FIRST AID:

EYES: Flush eyes with plenty of water for at least 5 minutes. No adverse effects anticipated by this route of exposure except for potential frostbite. Consult Medical personnel

SKIN: If shoes, gloves, or clothing covering skin become wet with sulfuryl fluoride, immediately apply water to contaminated clothing before removing. Once area has thawed, remove contaminated items covering skin. Wash thoroughly or shower.

INGESTION: No adverse effects anticipated by this route of exposure.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Distributed by: THE INDUSTRIAL FUMIGANT CO. P.O. Box 1200, Olathe, KS 66051-1200 1-800-477-4432 • (913) 782-6299 FAX



VIKANE* GAS FUMIGANT

Emergency Phone: 800-992-5994 Dow AgroSciences LLC Indianapolis, IN 46268

Effective Date: 5/22/01 Product Code: 91503 MSDS: 000506

NOTE TO PHYSICIAN: Supportive care. Treatment based on judgment of the physician in response to reactions of the patient. Sulfuryl fluoride is a gas, which has no warning properties such as odor or eye irritation (however, chloropicrin is used as a warning agent and is a known lachrymator). The prediction of possible human effects is based in part on observations made on laboratory animals. It is predicted that persons exposed to sulfuryl fluoride will show little evidence of intoxication at first, unless the concentration is very high (>400 ppm). Early symptoms of exposure to sulfuryl fluoride are respiratory irritation and central nervous system depression. Excitation may follow. Slowed movement, reduced awareness, and slow or garbled speech may be noted. It is essential to keep such an individual at bed rest for at least 24 hours. Clinical observations should be directed at the pulmonary, hepatic, and renal systems. Prolonged exposure can produce lung irritation, pulmonary edema, nausea, and abdominal pain. Repeated exposure to high concentrations can result in significant lung and kidney damage. Convulsions may ensue with respiratory arrest being the terminal event. Assisted respiration may be necessary. Clinical observation is essential. There is no known antidote for over-exposure to sulfuryl fluoride.

5. FIRE FIGHTING MEASURES:

FLASH POINT: Not applicable **METHOD USED**: Not applicable

FLAMMABLE LIMITS

LFL: Not combustible UFL: Not combustible

EXTINGUISHING MEDIA: Sulfuryl fluoride is not combustible. However, if cylinders are in a fire area, water can be used to keep them cool to help prevent discharge of product caused by melted fusible plugs on the cylinders. Use of water will also help to scrub out part of any hydrofluoric acid and sulfur dioxide, which may be formed by decomposition of the product in a fire.

FIRE & EXPLOSION HAXARDS: Cylinders exposed to fire may vent and release toxic gas through melted fusible plugs on cylinders. Although sulfuryl fluoride is not combustible, in temperatures exceeding 400°C (752°F), it will degrade to form hydrogen fluoride and sulfur dioxide.

FIRE-FIGHTING EQUIPMENT: Wear positive-pressure, self-contained breathing apparatus and full protective clothing. When fighting fires in atmospheres containing potentially high concentrations of sulfuryl fluoride, encapsulating protective suits should be worn due to possible formation of hydrofluoric acid. Protective suit material should be compatible with exposure to hydrofluoric acid.

6. ACCIDENTAL RELEASE MEASURES:

ACTION TO TAKE FOR SPILLS/LEAKS: Evacuate immediate area if cylinder begins to leak. Use a NIOSH or MSHA approved positive-pressure, self-contained breathing apparatus (SCBA) or combination air-supplied/SCBA respirator, such as manufactured by Ranger, Survivair, Scott, or MSA, for entry into affected areas to correct problem. For leaking cylinders occurring near structure being fumigated, place the cylinder inside the designated structure if it can be done safely. If leaking cylinder occurs elsewhere, move leaking or damaged cylinder outdoors or to an isolated location, observing strict safety precautions. Work upwind if possible. Do not permit entry into leakage area by unprotected persons until concentration of fumigant is determined to be 5 ppm or less, as determined by a detection device with sufficient sensitivity such as an INTERSCAN or MIRAN gas analyzer. For detailed information on the source and use of air monitoring devices or respirators, consult Dow AgroSciences at 800-992-5994.

7. HANDLING AND STORAGE:

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Handling: Keep out of reach of children. Do not breathe gas. Keep all unnecessary people and pets out of area containing sulfuryl fluoride gas. Storage: Store in original container and away from heat and dwellings.



VIKANE* GAS FUMIGANT

Emergency Phone: 800-992-5994 Dow AgroSciences LLC

Indianapolis, IN 46268

Effective Date: 5/22/01 Product Code: 91503 MSDS: 000506

8. EXPOSURE CONTROLS/PERSONAL PROTECTION: ||9. PHYSICAL AND CHEMICAL PROPERTIES:

These precautions are suggested for conditions where a potential for exposure exists. Emergency conditions may require additional precautions.

EXPOSURE GUIDELINE: Sulfuryl fluoride: ACGIH TLV and OSHA PEL are 5 ppm TWA, 10 ppm STEL. PELs are in accord with those recommended by OSHA, as in the 1989 revision of PELs.

ENGINEERING CONTROLS: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Lethal concentrations may exist in areas with poor ventilation.

RECOMMENDATIONS FOR MANUFACTURING, COMMERCIAL BLENDING, AND PACKAGING WORKERS:

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below exposure guideline. When respiratory protection is required for certain operations, use a NIOSH approved positive-pressure supplied-air respirator. For emergency and other conditions where the exposure guideline may be greatly exceeded, use a NIOSH approved positive pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. In confined or poorly ventilated areas, use a NIOSH approved positive-pressure supplied-air respirator.

SKIN PROTECTION: No special skin protection should be needed. Skin contact with the liquid may cause freeze damage if the liquid is confined to the skin; do not wear gloves or rubber boots.

EYE PROTECTION: Wear chemical goggles.

APPLICATORS AND ALL OTHER HANDLERS: Refer to the product label for personal protective clothing and equipment.

BOILING POINT: -67°F (-55°C)

VAPOR PRESSURE: 15.2 atmospheres @ 20°C

VAPOR DENSITY: 4.3 g/L @ 20°C

SOLUBILITY IN WATER: Practically insoluble

SPECIFIC GRAVITY: 1.35 @ 20°C

APPEARANCE: Colorless

ODOR: Odorless compressed gas

10. STABILITY AND REACTIVITY:

STABILITY: (CONDITIONS TO AVOID) Cylinders may leak or rupture in a fire.

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID) Strong base.

HAZARDOUS DECOMPOSITION PRODUCTS: Sulfur dioxide and hydrogen fluoride under fire conditions with hydrocarbons.

HAZARDOUS POLYMERIZATION: Not known to occur.

11. TOXICOLOGICAL INFORMATION:

MUTAGENICITY: In-vitro and animal mutagenicity studies were negative.

12. ECOLOGICAL INFORMATION:

ENVIRONMENTAL FATE:

MOVEMENT & PARTITIONING:

Bioconcentration potential is low (BCF <100 or Log Pow <3).

Potential for mobility in soil is very high (Koc between 0 and 50).

Log octanol/water partition coefficient (Log Pow) is estimated using a structural fragment method to be 0.41. Soil organic carbon/water partition coefficient (Koc) is estimated to be 6.124.

Henry's Law Constant (H) is estimated to be 3.28E-02 atm- M^3 /mole.

DEGRADATION & PERSISTENCE:

The hydrolysis half-life is 18 minutes to 3 days.



VIKANE* GAS FUMIGANT

Emergency Phone: 800-992-5994 Dow AgroSciences LLC

Indianapolis, IN 46268

Effective Date: 5/22/01 Product Code: 91503 MSDS: 000506

ECOTOXICOLOGY:

Due to rapid dispersion, no significant effects are expected in the aquatic environment.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHOD: Promptly return all empty cylinders to Dow AgroSciences. Wastes are toxic. Improper disposal of excess waste is a violation of federal law. If these wastes can not be disposed of by use according to label instruction, consult your state pesticide or the hazardous waste representative at the nearest EPA regional office for guidance.

14. TRANSPORT INFORMATION:

For DOT regulatory information, if required, consult transportation regulations, product-shipping papers, or consult your Dow AgroSciences representative.

15. REGULATORY INFORMATION:

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations.

U.S. REGULATIONS

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	CONCENTRATION

Sulfuryl Fluoride 002699-79-8 99.8%

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

An immediate health hazard A delayed health hazard A sudden release of pressure hazard A reactive hazard

TOXIC SUBSTANCES CONTROL ACT (TSCA): All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

STATE RIGHT-TO-KNOW: The following product components are cited on certain state lists as mentioned. Non-listed components may be shown in the composition section of the MSDS.

	CHEMICAL NAME	CAS NUMBER	LIST
--	---------------	------------	------

Sulfuryl Fluoride 002699-79-8 NJ3 PA1

NJ3=New Jersey Workplace Hazardous Substance (present at > or = to 1.0%).

PA1=Pennsylvania Hazardous Substance (present at > or - to 1.0%).

OSHA HAZARD COMMUNICATION STANDARD: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATINGS:

Category	Rating
Health Flammability Reactivity	3 0 1
•	



VIKANE* GAS FUMIGANT

Emergency Phone: 800-992-5994

Dow AgroSciences LLC Indianapolis, IN 46268

Effective Date: 5/22/01 Product Code: 91503 MSDS: 000506

COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA, or SUPERFUND): To the best of our knowledge, this product contains no chemical subject to reporting under CERCLA.

16. OTHER INFORMATION:

MSDS STATUS: Revised Section: 8

Reference: DR-0015-5588 Replaces MSDS dated: 02/20/01 Document Code: D03-069-446

Replaces Document Code: D03-069-445

The Information Herein Is Given In Good Faith, But No Warranty, Express or Implied, Is Made. Consult Dow AgroSciences for Further Information.